

SONALIKA

HEAVY DUTY TRACTOR RANGE «FOR YOUR FIELD»

26 HP



RELIABLE MECHANICAL
TRACTOR

POWER PACKED
ENGINE

AERODYNAMIC
BONNET

AGRI, IND. & TURF
TYRE OPTION

REINFORCED SAFETY
FEATURES



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

HEAVY DUTY TRACTOR RANGE « FOR YOUR FIELD »

26 HP

SONALIKA



FEATURES	Sonalika 26 HP
ENGINE	
Engine Type	Mitsubishi 3 Cylinder Engine
HP Category	26
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM	2700
Air cleaner	Dry type with clogging Sensor
Cold Start	Standard
Max Torque (Nm)	76.3
Exhaust	Downdraft
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	15.58 @ 2700 erpm
Minimum Speed (Km/Hr)	1.67 @ 2700 erpm
BRAKES	
Brakes	Oil Immersed Brakes
Type of actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Mechanical, Foot Operated
PTO	
PTO (RPM)	540, 1000
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 65Ah
Type of Actuation	12V, 42Amp
Seven Pin Trailer Socket	Output 12V
HYDRAULICS	
3 Point Linkage	Cat-I
Stay Bars	Anchor Chain
Lifting Capacity	600Kg
Auxiliary Hydraulic Circuit	1DA
SAFETY SWITCH	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard

FEATURES	Sonalika 26 HP
CAPACITY (LTRS)(+/-5%)	
Fuel Tank (Lit)	26
TURNING RADIUS	
Without Brakes (m)	3.1
TYRE	
Front	6.00-12
Rear	8.30-20
DIMENSIONS & WEIGHT(+/-5%)	
Weight (Kg)	1020
Wheel Base (mm)	1560
Total Length (mm)	2760
Total Width (mm)	1075
Height (mm) Up to ROPS	1955
Min Ground Clearance (mm)	240
Front Track (mm)	885
Rear Track (mm)	835
OTHERS	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard
Front & Rear Weights with Std. Ballast	Front weights-15x2
Trailer Hitch	1. Clevis Hitch 2. Swinging Drawbar (Optional)
ROPS	Standard
OPTIONAL FEATURES	
TURF TYRES:	Front Tyre - 23x8.50-12
	Rear tyre - 33x15.50 - 16.5
INDUSTRIAL TYRES:	Front tyre- 23x8.50-12
	Rear tyre- 33x15.50-16.5
AGRI TYRES:	Front tyre- 6X12
	Rear tyre- 8.3X20
RADIAL AGRI TYRES:	Front tyre- 6.5/80-12
	Rear tyre- 280/70 R18
GALAXY PRO TYRES:	Front tyre- 220/55R12
	Rear tyre- 280/70 R16
Front End Loader	Optional

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, please correlate with latest updates. Accessories shown may not be part of standard product.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India) | Phone: +91 11 66 45 5200 |
Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) Phone: +91 01882 522220/ 522221 | Fax: +91 01882 522222
Email: exports@sonalika.com | URL: www.international.sonalika.com