

SONALIKA

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

26 HP



RELIABLE MECHANICAL
TRACTOR

POWER PACKED
ENGINE

TWIN PROJECTOR
HEADLAMPS

AGRI, IND. & TURF
TYRE OPTION

REINFORCED SAFETY
FEATURES



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR



26HP

SONALIKA



FEATURES	S 26
Model Description	SONALIKA 26
ENGINE	
Engine Type	Mitsubishi 3 Cylinder Engine
HP Category	26
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM	2700
Air cleaner	Dry
Cold Start	Standard
Max Torque (nm)	76.3 @ 2700
Exhaust	Underhood Downdraft Silencer
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	14.04 @ 2700
Minimum Speed (Km/Hr)	1.50 @ 2700
BRAKES	
Brakes	Oil Immersed Brakes
Type of actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Yes, Foot Operated
PTO	
PTO (RPM)	540, 1000
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 65Ah
Type of Actuation	12V, 42Amp
Parking Brake	Standard
HYDRAULICS	
3 Point Linkage	Cat-I
Stay Bars	Anchor Chain
Lifting Capacity	600Kg
Auxiliary Hydraulic Circuit	1DA/ 1SA (Optional)
Lift Rods	Standard

FEATURES	S 26
Flow(LPM)	18
SAFETY SWITCH	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
CAPACITY (LTRS)(+/-5%)	
Fuel Tank (Lit)	26.5
TURNING RADIUS	
Without Brakes (m)	2.3
TYRE	
Front	6.00-12
Rear	8.30-20
DIMENSIONS & WEIGHT(+/-5%)	
Weight (Kg)	960
Wheel Base (mm)	1560
Total Length (mm)	2725
Total Width (mm)	1058
Height (mm) Up to ROPS	2153
Min Ground Clearance (mm)	255
Front Track (mm)	894
Rear Track (mm)	825
OTHERS	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard
Front & Rear Weights with Std. Ballast	Front weights-15x2
Trailer Hitch	1. Clevis Hitch
	2. Swinging Drawbar (Optional)
ROPS	Standard
OPTIONAL FEATURES	
Tyres	TURF TYRES: Front Tyre - 23x8.50-12 Rear Tyre - 33x15.50-16.5
	INDUSTRIAL TYRES: Front Tyre- 23x8.50-12 Rear Tyre- 33x15.50-16.5

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, please correlate with latest updates. Accessories shown may not be part of standard product.

DEALER STAMP



SONALIKA S26 AF

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221

Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.solistractors.com/www.solisworld.com