



# SONALIKA

## Worldtrac 75 Rx



**POWERED  
TO  
PERFORM**

### SONALIKA WORLDTRAC SPECIFICATIONS

	STANDARD FEATURES	SONALIKA WORLDTRAC 75 Rx
Engine	Engine Type	4100 FLT with coldstart
	HP Category	75
	No. of Cylinders	4
	Aspiration	Turbo Charged
	Cubic Capacity (cc)	3707
	Rated RPM (+/-25mm)	2200
	Air cleaner	Dry air cleaner with clogging sensor
Transmission	Max Torque @ RPM(Nm)	278(+/-5%)@1200 RPM(+/-100)
	Drive	2WD/4WD
	Clutch	Double Clutch
	Gearbox	12F+12R
Speed (Forward)	Transmission	Synchromesh
	Maximum (Speed Km/Hr)	31.33@2200
Brakes	Minimum (Speed Km/Hr)	1.52@2200
	Brakes	Oil immersed brakes
Differential lock	Type of actuation	Mechanical
	Hand brake	Independent
PTO	Differential lock	Mechanical, foot operated
	PTO (rpm)	540,540E with independent PTO.
DCV	PTO (actuation)	Mechanical, Hand operated
	Auxiliary hydraulic circuit	25A/2DA
Steering	No. of Spool valves	4
	Steering	Power Steering
Electrical	Battery	12 V,110 AH
	Alternator	12V
Three Point Linkage	Seven pin trailer socket	Yes
	3 point linkage	CAT2
Safety Switch	Stay Bars	Yes floating type
	Hydraulic lifting capacity	2500 kg
Capacity (ltrs)(+/-5%) approx	Neutral safety switch	Yes
	P.T.O Safety switch	Yes
Turning Diameter	Clutch Safety Switch	Yes
	Fuel tank (Lit)	76
Tyre	Eng Oil (Lit)	10.75
	Turning diameter. With Brakes (m)	7.97 m ( R ) - 7.75 m ( L )/8.85 m ( R ) - 9.30 m ( L )
Dimension & Weight(+/-5%)	Without Brakes (m)	9.52 m ( R ) - 9.45 m ( L )/ 10.00 m ( R ) - 10.78 m ( L )
	Front	7.5x16/ 11.2x24
	Rear	16.9x30
	Weight(kg)	2845/3075 (Unballasted)
	Wheel Base (mm)	2250/2355
	Total Length (mm)	3930/3970
	Total Width (mm)	1940(min)-2350(max)
	Height (mm)	2600(ROPS)
	Min Ground Clearance (mm) min	370/375
	Front Track (mm)	1360-1715/1480-1830
Others	Rear Track (mm)	1440-1910
	Fuel Indicator gauge	Yes
	Registration Plate with light	Yes with E-marked light
	Front Toe Hook	Yes
	ROPS	Yes
	Front & rear weights	Front base weight 72 kg+ 6x31 kg front removable weights and rear 1x34 kg on each rear wheel
	Trailer hitch	Rear Rotating tow hook
Drawbar	Swinging draw bar with Linkage crossbar	
Canopy	Yes	

#### SALIENT FEATURES



**Independent P.T.O. Gash**  
\*For better output in P.T.O. operations  
\*Easy start and stop of clutch



**Instrument Cluster**  
\*All the indicators located in a single unit  
\*Better operation



**Aerodynamic Shape with Spoiler Platform**  
\*Better stability  
\*Better access to controls



**Dry Air Cleaner with Clogging sensor**  
\*Clogging sensor indicator provided as cluster for checked position, which helps for better maintenance of tractor.



**Higher Lifting Capacity 2500kg. Best in its Class**  
\*For lifting higher loads in commercial applications



**Heavy duty MFWD Front Axle**  
\*Rigid traction  
\*For sustaining heavier loads  
\*Power steering for easy operation & operator control



**Synchromesh Gear Box with 12x12 speeds**  
\*Directional shifter more suitable for commercial application & easy for operator  
\*Smooth shifting



**Powerful & Fuel Efficient Engine**  
\*4 Stroke turbo charger  
\*Better fuel economy in its class.

#### INTERNATIONAL TRACTORS LIMITED

Corporate office : Pankaj Plaza-1, Plot no. 2, Karkardooma Community Centre, Commercial Complex, New Delhi-110092, (INDIA)

Tel: +91-11-22373785, 89, 91, Fax: +91-11-22377472, 22370492  
Works : Jalodhar Road, Hoshiarpur Punjab-146022, India, Tel: +91-1882-302523  
Fax: +91-1882-302523, e-mail : export@sonalika.com www.sonalika.com