

SONALIKA

HEAVY DUTY TRACTOR RANGE FOR YOUR FIELD

125 HP



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR

SONALIKA

HEAVY DUTY
TRACTOR RANGE
FOR YOUR FIELD

125 HP



FEATURES		Sonalika 125 HP
ENGINE		
HP Category	125 HP	
No. of Cylinders	6	
Displacement cc	6.127 L	
Aspiration	Turbocharged with Intercooler	
Bore/Stroke (mm)	105 x 118	
Rated RPM	2200	
Air Cleaner	Three stage dry type	
Max Torque	475	
TRANSMISSION		
Drive	4WD	
Clutch	Double Clutch	
Gearbox	24F+24R	
Transmission	Synchromesh Gear Box	
4WD Engagement	Electrical Switch Operated	
SPEED (FORWARD)		
Min Speed (km/h)	0.67 Kmph	
Max Speed (km/h)	40 Kmph	
Driver Seat	Mechanical Suspension	
Brakes		
Brakes	Wet Disk Brakes	
Type of Actuation	Hydraulic Actuated	
Hand Brake	Mechanical, Hand operated	
Trailer Brakes	HTB (Standard)	
DIFFERENTIAL LOCK		
Differential Lock	Electrical Switch Operated	
PTO		
PTO (RPM)	540/540E 540/1000 (optional)	
PTO (Actuation)	Mechanical Operated Lever	
STEERING		
Steering	Power	
ELECTRICAL		
Battery	12V, 110Ah	
Alternator	12V, 90A	
Seven Pin Trailer Socket	Yes	
HYDRAULICS		
Position & Draft Control	Electronic Lift (EHR)	
3 Point Linkage	CAT-II	
Lifting Capacity (kg)	4500	
Auxiliary Hydraulic Circuit	3DA, 2 SA convertible with 1 Detent	

FEATURES		Sonalika 125 HP
SAFETY SWITCH		
Neutral Safety Switch	Standard	
P.T.O Safety Switch	Standard	
Clutch Safety Switch	Standard	
CAPACITY (LTRS)(+/-5%) APPROX		
Fuel Tank (Ltr)	150	
TURNING RADIUS IN (m)		
Without Brakes & With Brakes	6.2 (w/o brakes)	
TYRE		
Tyres	Front: 380/85R24 Rear: 460/85R34	
DIMENSION & WEIGHT (+/-5%)		
Gross Weight (kg)	4665	
Wheel Base (mm)	2645	
Total Length (mm)	4660	
Total Width (mm)	2260	
Height (mm)	2660	
Ground Clearance (mm) min	488	
Front Track (mm)	1760	
Rear Track (mm)	1724	
OTHERS		
Fuel Indicator Gauge	Standard	
Registration Plate with Light	Standard	
Front Toe Hook	Standard	
Front & Rear Weights (kg)	Front 31x8+72 Base weight Rear 40x2	
Drawbar	Yes, Ladder Hitch	
Cabin	Standard	
OPTIONAL FEATURES		
ROPS	Optional	
Canopy	Optional	
Front Mudguard	Standard	
Weight optional (kg)	Front 31x10	

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com