

# SONALIKA

## HEAVY DUTY TRACTOR RANGE «FOR YOUR FIELD»

### 26 HP



RELIABLE MECHANICAL  
TRACTOR

POWER PACKED  
ENGINE

TWIN PROJECTOR  
HEADLAMPS

AGRI, IND. & TURF  
TYRE OPTION

REINFORCED SAFETY  
FEATURES



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**

# HEAVY DUTY TRACTOR RANGE FOR YOUR FIELD

## 26 HP

# SONALIKA



FEATURES		Sonalika 26 HP
<b>ENGINE</b>		
Engine Type	MHI Engine	
HP Category	26	
No. of Cylinders	3	
Aspiration	Natural	
Cubic Capacity (cc)	1318	
Rated RPM	2700	
Air Cleaner	Dry Type with Clogging Sensor	
Cold Start	Standard	
Max Torque (Nm)	76.3 Nm	
Exhaust	Downdraft Exhaust	
Muffler	Under-hood	
<b>TRANSMISSION</b>		
Drive	4WD	
Clutch	Single Clutch	
Gearbox	6F+2R	
Front Axle	4WD	
Transmission	Sliding Mesh	
<b>SPEED (FORWARD)</b> Agri Tyre		
Maximum Speed (Km/Hr)	18.08	
Minimum Speed (Km/Hr)	1.67 @ 2700 erpm Speeds May Vary with Other Tyres	
<b>Brakes</b>		
Brakes	Oil Immersed Brakes	
Type of Actuation	Mechanical	
Parking Brake	Independent	
<b>DIFFERENTIAL LOCK</b>		
Differential Lock	Mechanical, Foot Operated	
<b>PTO</b>		
PTO (RPM)	540/1000	
PTO (Actuation)	Mechanical	
<b>STEERING</b>		
Steering	Power	
<b>ELECTRICAL</b>		
Battery	12V, 65Ah	
Alternator	12V, 42Amp	
Seven Pin Trailer Socket	Output 12V	
<b>HYDRAULICS</b>		
3 Point Linkage	Cat 1-N	
Stay Bars	Anchor Chain	
Hydraulic Lifting Capacity (Kg)	600	
Auxiliary Hydraulic Circuit	1DA	
<b>SAFETY SWITCH</b>		
Clutch Safety Switch	Standard	

FEATURES		Sonalika 26 HP							
PTO Safety Switch	Standard								
Neutral Safety Switch	Standard								
<b>CAPACITY (Ltrs.) (+/-5%)</b>									
Fuel Tank (Ltr.)	26								
<b>TURNING RADIUS</b>									
With Brakes (m)	2.7								
<b>TYRE</b>									
Front	6.00 - 12								
Rear	8.30 - 20								
<b>DIMENSION &amp; WEIGHT (+/-5%) Agri Tyre</b>									
Weight (Kg)	995								
Wheel Base (mm)	1560								
Total Length (mm)	2760								
Total Width (mm)	1075								
Height (mm) Up to ROPS	1955								
Min. Ground Clearance (mm)	240								
Front Track (mm)	885								
Rear Track (mm)	835								
<b>OTHERS</b>									
Fuel Indicator Gauge	Standard								
Front Tow Hook	Standard								
Front & Rear Weights with Std. Ballast (kg)	Front Weights 15x2								
Trailer Hitch	1. Swinging Bar (Optional) 2. Clevis Hitch (Standard) 3. Semi Automatic Hitch								
ROPS	Standard								
<b>OPTIONAL FEATURES</b>									
<b>TYRES</b>									
	<b>TURF</b> Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5		<b>INDUSTRIAL</b> Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5		<b>AGRI</b> Front Tyre: 7x14 Rear Tyre: 8.3x24		<b>RADIAL</b> Front Tyre: 6.5/80-12 Rear Tyre: 280/70 R18		<b>GALAXY PRO</b> Front Tyre: 220/55 R12 Rear Tyre: 280/70 R16
Front End Loader	Optional	Canopy	Optional						

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)  
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221  
Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com