

SONALIKA

HEAVY DUTY TRACTOR RANGE FOR YOUR FIELD

75 HP



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION WITH
YANMAR

SONALIKA

HEAVY DUTY
TRACTOR RANGE
FOR YOUR FIELD

75 HP



FEATURES		Sonalika 75 HP	
ENGINE		Sonalika 75 HP	
HP Category	75		
Emission	Stage 2 / Stage 3		
No. of Cylinders	4		
Aspiration	Turbocharged		
Cubic Capacity (cc)	3707		
Rated RPM	2200/2000		
Air Cleaner	Dry Air Cleaner		
Cold Start	Standard		
Max Torque (Nm)	278 Nm @1200 289 Nm @1300		
Exhaust	Upward		
Muffler	Underhood		
TRANSMISSION		Sonalika 75 HP	
Drive	4WD / 2WD		
Clutch	Dual Clutch, Dry Friction Plate		
Gearbox	8F+2R		
Front Axle	4WD		
Transmission	Constant Mesh		
SPEED (FORWARD)		Sonalika 75 HP	
Maximum Speed (Km/Hr)	36.46 @ 2200 erpm		
Minimum Speed (Km/Hr)	1.95 @ 2200 erpm		
Brakes		Sonalika 75 HP	
Brakes	Oil Immersed Brake		
Type of Actuation	Mechanical		
Parking Brake	Independent Type		
DIFFERENTIAL LOCK		Sonalika 75 HP	
Differential Lock	Mechanical, Foot Operated		
PTO		Sonalika 75 HP	
PTO (RPM)	540@1680		
PTO (Actuation)	Mechanical		
STEERING		Sonalika 75 HP	
Steering	Power		
ELECTRICAL		Sonalika 75 HP	
Battery	12V, 110 AH		
Alternator	12V, 36Amps		
Seven Pin Trailer Socket	Output 12V		
HYDRAULICS		Sonalika 75 HP	
3 Point Linkage	CAT-II		
Hydraulic Lifting Capacity (kg)	2000		
Auxiliary Hydraulic Circuit	2DA		
FEATURES		Sonalika 75 HP	
SAFETY SWITCH		Sonalika 75 HP	
Neutral Safety Switch	Standard		
CAPACITY (Ltrs.) (+/-5%)		Sonalika 75 HP	
Fuel Tank (Ltr.)	65		
TURNING RADIUS		Sonalika 75 HP	
Without Brakes (m)	5.34		
TYRE		Sonalika 75 HP	
Front	11.2x24 (4WD)		
Rear	16.9x30		
DIMENSION & WEIGHT (+/-5%)		Sonalika 75 HP	
Weight (kg)	3120		
Wheel Base (mm)	2310		
Total Length (mm)	4190		
Total Width (mm)	1980		
Height (mm) Up to ROPS	2710		
Min. Ground Clearance (mm)	400		
Front Track (mm)	1670		
Rear Track (mm)	1500		
OTHERS		Sonalika 75 HP	
Fuel Indicator Gauge	Standard		
Front Tow Hook	Standard, Inbuilt in Front Weights		
Standard Weight (kg)	Front 30x2+25x4 Rear 1x34 on Each Tyre		
Cabin	Standard		
OPTIONAL FEATURES		Sonalika 75 HP	
ROPS	Optional		
Canopy	Optional		
Tyre	Front Tyre: 7.5x16 Rear Tyre: 16.9x30		

Sonalika 75RX (8+2) in Non Turbo Engine

Aspiration	Natural Aspiration
Emission	Stage 2
Max. Torque (Nm)	272 @ 1300
Rated RPM	2200
Cubic Capacity (cc)	4087

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
 Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
 Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.