

**HEAVY DUTY  
TRACTOR RANGE  
FOR YOUR FIELD**

**PERFECTED FOR  
HAULAGE AND  
AGRICULTURAL  
NEEDS**

**VALUE FOR MONEY  
EXTRA DURABILITY  
DIVERSE APPLICATIONS**

**FP-18**



**Engine**

- Fuel Efficient, Single Cylinder 863cc Engine

**Hydraulics**

- Powerful High Lift Capacity of 700 Kg

**Transmission**

- Tough Transmission  
6 Forward + 2 Reverse Speeds

**Compact Design**

- Ideal for Sugarcane, Cotton etc.

# SPECIFICATIONS

FEATURES	Sonalika FP-18
<b>ENGINE</b> 	
HP Category	18
No of Cylinder	1
Aspiration	Natural
Cubic Capacity	863.5 cc
Rated RPM	2300 ± 75
Air Cleaner	Dry type
Max Torque (Nm)	54@1200±200 RPM
Exhaust	Downdraft
<b>TRANSMISSION</b> 	
Drive	2WD
Gearbox	Sliding Mesh
Transmission	6F + 2R
<b>SPEED (FORWARD)</b> 	
Minimum Speed (Km/hr)	2.01
Maximum Speed (Km/hr)	25.19
<b>Brakes</b>	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent Parking Brakes
<b>PTO</b> 	
PTO (RPM)	540 & 540E
PTO (Actuation)	Mechanical
<b>STEERING</b> 	
Steering	Mechanical
<b>ELECTRICALS</b> 	
Battery	12V, 65 Ah
Alternator	12V, 36 H

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tires.

FEATURES	Sonalika FP-18
<b>HYDRAULICS</b> 	
3 Point Linkage	CAT 1
Stay Bars	Anchor Chain
Auxiliary Hydraulic Circuit	1TA
Lift Capacity (Kg)	700
Lift Rods	Standard
<b>CAPACITY (LITRES ± 5%)</b> 	
Fuel Tank (Ltr.)	28
<b>TYRE</b>	
Front	5.25 X 14
Rear	8 X 18
<b>OVERALL WEIGHT &amp; DIMENSIONS</b> 	
Weight (Kg)	1160
Wheel Base (mm)	1485
Total Length (mm)	2745
Total Width (mm)	1165
Height (mm) Up to Muffler	1780
Min. Ground Clearance	220
Front Track (mm)	970
Rear Track (mm)	935
<b>OTHERS</b> 	
Front Toe Hook	Yes, Available



DEALER STAMP



## INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)  
 Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221  
 Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com