

SONALIKA

HEAVY DUTY TRACTOR RANGE «FOR YOUR FIELD»

55 RX



AGILE 3 CYLINDER
ENGINE

OIL IMMERSSED
BRAKES

8F + 2R
SYNCHROMESH
TRANSMISSION

HEAVY LIFT
CAPACITY

SMART TECH
FEATURES



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**





55 RX

SONALIKA




FEATURES	Sonalika 55 RX
ENGINE	
Engine Type	3105EL Natural Aspirated
HP Category	55
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	3065
Rated RPM	2100
Air Cleaner	Dry Type with Clogging Sensor
Max Torque (Nm)	205 Nm
Exhaust	Updraft/Downdraft
Muffler	Underhood
TRANSMISSION	
Drive	2WD/4WD
Clutch	Dual Clutch
Gearbox	8F+2R
Transmission	Synchromesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	32.79 @ rated
Minimum Speed (Km/Hr)	2.50 @ rated
BRAKES	
Brakes	Oil Immersed Brake
Type of Actuation	Mechanical
Parking Brake	Independent Type
DIFFERENTIAL LOCK	
Differential Lock	Mechanical, Foot Operated
PTO	
PTO (RPM)	540 & Reverse
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 88Ah
Alternator	12V, 90Amp
Seven Pin Trailer Socket	Output 12V
HYDRAULICS	
3 Point Linkage	CAT-II
Stay Bars	Adjustable
Hydraulic Lifting Capacity (kg)	1600
Auxiliary Hydraulic Circuit	(1SA+1DA) 2DA
SAFETY SWITCH	
PTO Safety Switch	Standard
Neutral Safety Switch	Standard

FEATURES	Sonalika 55 RX
CAPACITY (Ltrs.) (+/-5%)	
Fuel Tank (Ltr.)	65
TURNING RADIUS	
Without Brakes (m)	3.58
TYRE	
Front	9.5x24
Rear	16.9x28
DIMENSION & WEIGHT (+/-5%)	
Weight (Kg)	2870
Wheel Base (mm)	2190
Total Length (mm)	3590-3910
Total Width (mm)	1750-1850
Height (mm) Up to ROPS	2620-2630
Min. Ground Clearance (mm)	290
Front Track (mm)	1370
Rear Track (mm)	1420
OTHERS	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard, Inbuilt in Front Weights
Trailer Hitch	Swinging Bar (Standard)
ROPS	Standard
Canopy	Standard
OPTIONAL FEATURES	
Front & Rear Weights with Std. Ballast (kg)	Front Weight: 2x30 + 4x25 (4WD) 54 + 4x31(4WD) 51 + 6x29 (2WD) 51 + 4x29 (2WD) Rear Weight: 1x34 (on each wheel)
Tyres	2WD Front Tyre: 7.5x16 Rear Tyre: 14.9x28 Front Tyre: 7.5x16 Rear Tyre: 16.9x28 4WD Front Tyre: 9.5x24 Rear Tyre: 16.9x28
Cabin	Optional
Loader	Optional

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com