

# SONALIKA

## HEAVY DUTY TRACTOR RANGE «FOR YOUR FIELD»

# 60 HP



AGILE 3 CYLINDER  
ENGINE

8F+2R SWIFT  
SHIFT

HEAVY LIFT  
CAPACITY

PARALLELOGRAM  
LOADER OPTION

INTEGRATED SAFETY  
HVAC CABIN (OPTIONAL)



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**



# HEAVY DUTY TRACTOR RANGE «FOR YOUR FIELD»

## 60HP

# SONALIKA



| FEATURES                    | 60                 |
|-----------------------------|--------------------|
| Model Description           | Sonalika-60        |
| <b>ENGINE</b>               |                    |
| Engine Type                 | 3100 FLT           |
| HP Category                 | 60                 |
| No. of Cylinders            | 3                  |
| Aspiration                  | Turbo              |
| Cubic Capacity (cc)         | 2780               |
| Rated RPM                   | 2100               |
| Air cleaner                 | Dry Type           |
| Cold Start                  | Standard           |
| Max Torque (Nm)             | 230Nm@1300rpm      |
| Exhaust                     | Underhood / Upward |
| <b>TRANSMISSION</b>         |                    |
| Drive                       | 4WD                |
| Clutch                      | Dual Clutch        |
| Gearbox                     | 8F+2R              |
| Front Axle                  | 4WD                |
| Transmission                | Swift Shift        |
| <b>SPEED (FORWARD)</b>      |                    |
| Maximum Speed (Km/Hr)       | 33.67              |
| Minimum Speed (Km/Hr)       | 2.52               |
| <b>BRAKES</b>               |                    |
| Brakes                      | Oil Immersed Brake |
| Type of actuation           | Mechanical         |
| Parking Brake               | Independent Type   |
| <b>DIFFERENTIAL LOCK</b>    |                    |
| Differential lock           | Standard           |
| <b>PTO</b>                  |                    |
| PTO (rpm)                   | 540                |
| <b>STEERING</b>             |                    |
| Steering                    | Power              |
| <b>ELECTRICAL</b>           |                    |
| Battery                     | 12V, 88Ah          |
| Alternator                  | 12V, 36Amp         |
| Seven pin trailer socket    | Standard           |
| <b>HYDRAULICS</b>           |                    |
| 3 point linkage             | CAT-II             |
| Stay Bars                   | Swinging Drawbar   |
| Hydraulic lifting capacity  | 2000 kg            |
| Auxiliary hydraulic circuit | 2DA                |
| Lift rods                   | Standard           |

| FEATURES                               | 60                                |
|----------------------------------------|-----------------------------------|
| <b>SAFETY SWITCH</b>                   |                                   |
| Clutch Safety Switch                   | Standard                          |
| PTO Safety Switch                      | Standard                          |
| Neutral Safety Switch                  | Standard                          |
| <b>CAPACITY (LTRS)(+/-5%)</b>          |                                   |
| Fuel tank (Lit)                        | 62                                |
| <b>TYRE</b>                            |                                   |
| Front                                  | 9.5-24                            |
| Rear                                   | 16.9X28                           |
| <b>DIMENSION &amp; WEIGHT(+/-5%)</b>   |                                   |
| Weight(kg)                             | 2500                              |
| Wheel Base (mm)                        | 2350                              |
| Total Length (mm)                      | 3980                              |
| Total Width (mm)                       | 1790-1950                         |
| Height (mm) Up to ROPS                 | 2650                              |
| Min Ground Clearance (mm)              | 360                               |
| Front Track (mm)                       | 1295-1650                         |
| Rear Track (mm)                        | 1420-1880                         |
| <b>OTHERS</b>                          |                                   |
| Fuel Indicator gauge                   | Standard                          |
| Front Tow Hook                         | Standard, inbuilt in front weight |
| Front & rear weights with std. Ballast | Base Weight 72Kg+Front 6X31 Kg    |
| Trailer Hitch                          | Swinging Drawbar                  |
| ROPS                                   | Standard                          |
| <b>OPTIONAL FEATURES</b>               |                                   |
| Tyres                                  | Rear 9.5X20 / 16.9X28             |

\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

DEALER STAMP



## INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com