


SONALIKA

— THE TOUGHEST —
PERFORMER
« FOR YOUR FIELD »

90HP



ORCHARD/VINEYARD
FARMING SPECIALIST

TURBO CHARGED WITH
INTER COOLER ENGINE

HEAVY LIFT
CAPACITY

CARRARO
DRIVE LINE

HVAC CABIN
(OPTIONAL)



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH
YANMAR**



90HP

SONALIKA



FEATURES	N 90
Model Description	SONALIKA N90
ENGINE	
Engine Type	4105 ELT, Turbo Charged with Inter Cooler Engine
HP Category	90
No. of Cylinders	4
Aspiration	Turbo Charged
Cubic Capacity (cc)	4087
Rated RPM	2000
Air Cleaner	Dry Air Cleaner with Clogging sensor
Cold Start	Standard
Max Torque (Nm)	360 @ 1300
Exhaust	Underhood Downdraft towards the Floor
TRANSMISSION	
Drive	4WD
Clutch	Double Clutch
Gearbox	12F+12R
Front Axle	4WD
Transmission	Synchromesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	28.25 @ 2000
Minimum Speed (Km/Hr)	0.46 @ 2000
BRAKES	
Brakes	Oil Immersed Brake
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Standard, Foot Operated
PTO	
PTO (RPM)	540/ 540E
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V, 85Ah
Alternator	12V, 90Amp
Seven Pin Trailer Socket	Standard
HYDRAULICS	
3 Point Linkage	CAT-II
Stay Bars	Standard
Hydraulic Lifting Capacity	2500 Kg
Auxiliary Hydraulic Circuit	2DA/2SA
Lift Rods	Standard

FEATURES	N 90
SAFETY SWITCH	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
CAPACITY (LTRS) (+/-5%)	
Fuel Tank (Lit)	73
TURNING RADIUS	
Without Brakes (m)	3.6
TYRE	
Front	8-18
Rear	14.9-24
DIMENSIONS & WEIGHT(+/-5%)	
Overall Length (mm)	4240
Overall Width (mm)	1475
Overall Height upto ROPS (mm)	2700
Wheel Base (mm)	2306
Min. Ground Clearance	265
Front Wheel Track Agri (mm)	1150
Rear Wheel Track Agri (mm)	1082
Flange to Flange Distance Front/Rear	1155mm/892mm
OTHERS	
Fuel Indicator Gauge	Standard
Front Tow Hook	Yes, Inbuilt in Front Weight
Front & Rear Weights with Std. Ballast	Front-72 Kg base wt 31x6Kg Front Removal Weight. / Rear 2X30 Kg
Trailer Hitch	Swinging Drawbar
ROPS	Mid Mounted Foldable
OPTIONAL FEATURES	
Tyres	Front- 210/95/R18, Rear-360/70/R28 Front - 280/70R18, Rear- 360/70R28 Front - 260/70R16, Rear- 360/70R24
Cabin	HVAC / Heater
Front Mudguard	Standard
Trailer Brakes	HTB
Front Tyre 2WD	6.5x16

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, please correlate with latest updates. Accessories shown may not be part of standard product.

DEALER STAMP



SONALIKA N90 AF

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221

Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.sonalika.com/www.solisworld.com