

**SONALIKA**

**HEAVY DUTY  
TRACTOR RANGE**  
« FOR YOUR FIELD »

**26 HP**



**DIGITAL  
INSTRUMENT CLUSTER**

**AERODYNAMIC  
SHAPE BONNET**

**DRY AIR CLEANER  
WITH CLOGGING SENSOR**

**HIGH LIFTING  
CAPACITY**

**POWERFUL ENGINE  
LOW MAINTENANCE**



**COST  
EFFICIENT**

**MECHANICAL TRACTORS**

**MADE OF**

**REAL  
STEEL**

**STRATEGIC  
COLLABORATION  
WITH**










**YANMAR**







# HEAVY DUTY TRACTOR RANGE «FOR YOUR FIELD»

26 HP

SONALIKA



FEATURES	26 HP
<b>ENGINE</b> 	
Engine Type	3- Cyl. Mitsubishi Engine
HP Category	26
No. of Cylinders	3
Aspiration	Naturally
Cubic Capacity (cc)	1318
Rated RPM (+/-25mm)	2700
Air Cleaner	Dry air cleaner with clogging sensor
Cold Start	Standard
Max Torque (Nm)	75.2/2200
Exhaust	Horizontal
<b>TRANSMISSION</b> 	
Drive	4 WD
Clutch	Single Clutch
Gearbox	6 Forward + 2 Reverse
Transmission	Sliding Mesh
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr) 	17.97
Minimum Speed (Km/Hr)	1.98
Driver Seat	Adjustable
<b>BRAKES</b> 	
Brakes	Oil immersed brake
Type of Actuation	Mechanical
Parking Brake	Independent
<b>Differential Lock</b> 	
Differential Lock	Yes, Foot Operated
<b>PTO</b> 	
PTO (rpm)	540/540 E – 540 @ 2651 & 540E @ 2152
PTO (actuation)	Mechanical
<b>STEERING</b> 	
Steering	Power Steering
<b>ELECTRICAL</b> 	
Battery	12V, 65 Ah
Alternator	12V
Seven Pin Trailer Socket	Standard
<b>HYDRAULICS</b> 	
3 Point Linkage	Cat-1
Draft Control	Yes
Hydraulic Lifting Capacity	600Kg
Auxiliary hydraulic circuit	1SA

FEATURES	26 HP
<b>SAFETY SWITCH</b> 	
Clutch Safety Switch	Standard
<b>CAPACITY (LTRS)(+/-5%)</b> 	
Fuel Tank (Lit)	30
<b>TURNING RADIUS</b> 	
Without brakes (m) as per standard tyres	2.1(RHS) 2.3(LHS)
<b>TYRE</b> 	
Front	6X12
Rear	8.3*20
<b>DIMENSION &amp; WEIGHT(+/-5%)</b> 	
Weight (Kg)	910
Wheel Base (mm)	1565
Total Length (mm)	2705
Total Width (mm)	1070
Height (mm) Up to ROPS	1300
Min Ground Clearance (mm)	250
Front Track (mm)	894
Rear Track (mm)	825
<b>OTHERS</b> 	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard
Front Weights	30 Kg
Trailer hitch	Standard

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

DEALER STAMP



## INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India) | Phone: +91 11 66 45 5200 |  
Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) Phone: +91 01882 522220/ 522221 | Fax: +91 01882 522222  
Email: [exports@sonalika.com](mailto:exports@sonalika.com) | URL: [www.international.sonalika.com](http://www.international.sonalika.com)