

SONALIKA

HEAVY DUTY TRACTOR RANGE FOR YOUR FIELD

30 HP



HIGH LIFTING
CAPACITY

POWER PACKED
ENGINE

TWIN PROJECTOR
HEADLAMPS

AGRI, IND & TURF
TYRE OPTION

REINFORCED SAFETY
FEATURES



**COST
EFFICIENT**

MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH**

YANMAR

HEAVY DUTY TRACTOR RANGE FOR YOUR FIELD

30 HP



| FEATURES | 30 HP |
|-----------------------------|--------------------------------|
| Model Description | Sonalika-30 |
| ENGINE | |
| Engine Type | Mitsubishi Engine |
| HP Category | 30 |
| No. of Cylinders | 3 |
| Aspiration | Natural |
| Cubic Capacity (cc) | 1318 |
| Rated RPM | 3000 |
| Air cleaner | Dry with clogging Sensor |
| Max Torque (Nm) | 82 Nm(±5%) 2000 |
| Exhaust | Underhood Downdraft |
| TRANSMISSION | |
| Drive | 4WD |
| Clutch | Single Clutch |
| Gearbox | 6F+2R |
| Transmission | Sliding Mesh |
| SPEED (FORWARD) | |
| Maximum Speed (Km/Hr) | 17.06 Kmph (Varies with Tires) |
| Minimum Speed (Km/Hr) | 1.82 Kmph (Varies with Tires) |
| BRAKES | |
| Brakes | Oil Immersed |
| Type of actuation | Mechanical |
| Parking Brake | Latch Type |
| DIFFERENTIAL LOCK | |
| Differential lock | Foot Operated |
| PTO | |
| PTO (rpm) | Rear 540 & 1000 RPM |
| PTO (actuation) | Mechanical |
| STEERING | |
| Steering | Power |
| ELECTRICAL | |
| Battery | 12V, 65Ah |
| Alternator | 12V, 42Amp |
| HYDRAULICS | |
| 3 point linkage | Cat 1-N |
| Stay Bars | Anchor Chain |
| Lifting Capacity | 600Kg |
| Auxiliary hydraulic circuit | 1DA/ 1SA (optional) |
| Lift rods | Standard |

| FEATURES | 30 HP | | |
|---|---|---|--|
| Flow(LPM) | 14.8 | | |
| SAFETY SWITCH | | | |
| Clutch Safety Switch | Standard | | |
| CAPACITY (LTRS)(+/-5%) | | | |
| Fuel tank | 26.5 L | | |
| TURNING RADIUS | | | |
| Turning Radius (Meter) | 2.7 with Brake 3.0 without Brake | | |
| TYRE | | | |
| Front | 7X14 | | |
| Rear | 8.30-24 | | |
| DIMENSION & WEIGHT(+/-5%) | | | |
| Weight(kg) | 1030 | | |
| Wheel Base (mm) | 1570 | | |
| Total Length (mm) | 2760 | | |
| Total Width (mm) | 1165 | | |
| Height (mm) Up to ROPS | 2000 | | |
| Min Ground Clearance (mm) | 265 | | |
| Front Track (mm) | 950 | | |
| Rear Track (mm) | 870 | | |
| OTHER | | | |
| Trailer Hitch - Option 1 | Standard | | |
| - Option 2 | E-Marked Swinging bar | | |
| Front Tow Hook | Standard, Detachable | | |
| TYRE COMBINATIONS | | | |
| | | | |
| Agricultural Front 6x12 Rear 8.3x20 | Radial Agricultural Front 6.5/80-12 Rear 280/70 R18 | Turf & Ind. Front 23x8.5-12 Rear 33x15.5-16.5 | Ind. Galaxy Pro Front 220/55 R12 Rear 280/70 R16 |

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE. Please correlate with latest updates, accessories shown may not be part of standard product.

DEALER STAMP



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India) | Phone: +91 11 66 45 5200
 Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) Phone: +91 01882 522220/ 522221 | Fax: +91 01882 522222
 Email: exports@sonalika.com | URL: www.international.sonalika.com