

ROTAVATOR

SMART EDGE

SALIENT FEATURES














- International quality boron steel blades
- High tensile fasteners
- Flexible spring damper assembly
- Heavy duty gear box
- ✓ Powder coated paint
- ✓ Ensures smooth operation in different soil types
- ✓ Provides ease of working in interculture operations
- ✓ Effective for puddling due to better churning of soil



SMART EDGE

Rotavator is secondary tool used in preparing Seed Beds, Stubby ploughing in specially farming vineyard gardens.

TECHNICAL SPECIFICATIONS

	 Model Name	 Length (mm)	 Width (mm)	 Height (mm)	 Size (In Feet)	 Tillage Width (mm)	 Gear Box	 Side Transmission	 Type of Blade	 No of Blades	 No. of Flange's	 Weight (Kg. Approx)	 Tractor Power (HP)
Smart Edge	SL-SE 165	1810	929	1040	5.5	1650	Single Speed	Gear Drive	C & L Type	48	9	335	25-40
	SL-SE 185	2010	929	1040	6	1850				54	10	360	45-50
	SL-SE 205	2210	929	1040	7	2050				60	11	385	50-60



DUO CONE MECHANICAL SEAL SUITABLE FOR DRY & WET LANDS



SOIL STOPPER FOR SPILLING SOIL OUTSIDE



STRONG AND STURDY DESIGN FOR HASSLE FREE PERFORMANCE



WORKS PERFECT FOR PUDDLING IN PADDY FIELDS



SONALIKA

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
 Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221
 Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: www.international.sonalika.com

Auth. Dealer