SONALIKA

TRAILER

SALIENT FEATURES

- Heavy duty robust structure
- Easy to attach & detach with tractor
- Taper roller bearing used for long durability
- Corrugated sheet for better strength
- Heavy duty axle for robust field operations
- Optional hydraullic trailer brake

TRAILER

TECHNICAL SPECIFICATIONS

Description	SL-TT1.5	SL-TT1.5NT	SL-TT2	SL-TT2NT
Type of Trailer	Tipping	Non-Tipping	Tipping	Non-Tipping
Size (mm)	2134 X 1067 X 533		2134 X 1371 X 533	2134 X 1371 X 533
Main Chassis (mm)	100 X 50			
Bottom (mm)	3			
Side Sheet (mm)	2 Corrugated			
Axle (mm)	65			
Capacity (Ton)	1.5			
Tyre	6x16 Jeep Tyre			
Hydraulic Cylinder	N.A.			
Tractor (HP)	20/26		26	

CORRUGATED BODY PANEL SHEET

LEAF SPRING SUSPENSION

OPTIONAL ALL 4 SIDES OPENABLE

SONALIKA

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91 1882 302220, 302221
Fax: +91 1882 302293 | Email: exports@sonalika.com | URL: **www.international.sonalika.com**

Auth. Dealer