

CULTIVATOR

SINGLE SPRING LOADED SERIES













BENEFITS AND ADVANTAGES

- Efficient quick dumping lever with swinging rear gate helps in easy & effortless dumping
- The robust built of machine helps in easy collection of firewood, logs, hay & clearing debris
- The strong cutting steel base helps in easy penetration into soil

CULTIVATOR SINGLE SPRING LOADED SERIES

The robust design of single spring loaded series helps in breaking the clods & hard pans in the soil in the most efficient way. The greater tensile strength of the spring ensures the movement & resetting of the tine encountering obstacle perfectly. It is the best solution to work in the stony fields.

TECHNICAL SPECIFICATIONS

| |  Model |  No. of Tyne |  Frame (mm) |  Tyne Size (mm) |  Shovels (mm) |  Width (mm) |  Working Width (mm) |  Height (mm) |  Weight (Kg. Approx.) |  Tractor Power (HP) |
|-----------------------------|---|---|--|--|--|--|--|---|--|--|
| Single Spring Loaded Series | SL-CL-SS11 | 11 | 72x72x5 (Sq. Pipe) | 26 | 8(EN-45) | 2620 | 2570 | 1170 | 350 | 45-50 |
| | SL-CL-SS13 | 13 | | | | 3070 | 3020 | | 400 | 55-60 |
| | SL-CL-SS15 | 15 | | | | 3520 | 3470 | | 450 | 60-65 |
| | SL-CL-SS17 | 17 | | | | 3970 | 3920 | | 500 | 70-90 |



ROBUST FRAME ENSURES EFFICIENT WORKING IN THE TOUGHEST CONDITIONS



HEAVY DUTY SINGLE ACTING SPRING DESIGN WITH MORE STRENGTH ENSURES IDEAL MOVEMENT OF THE TYNE IN TOUGH CONDITIONS



HIGH CARBON STEEL REVERSIBLE SHOVEL ENSURES MINIMUM WEAR & GIVES MAXIMUM RELIABILITY



GREATER BEAM CLEARANCE HELPS TO COVER MORE WIDTH DURING OPERATION



SONALIKA

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | **Work:** Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | **Phone:** +91-01882-522220/ 522221

Fax:+91- 01882-522222 | **Email:** exports@sonalika.com | **URL:** www.international.sonalika.com

Auth. Dealer