## SONALIKA

# GROOMING MOWER



## **SALIENT FEATURES**

- Strong 3 point linkage suitable for cat I and cat II tractors
- Rollover wheel to avoid damages and extra support
- 3 equidistant blades with high tip speed for even cut

### **GROOMING MOWER**

Solis Grooming mower is the perfect machine to provide evenly cut grass in lawn. It can be easily rear mounted on the tractor & the 4 pivoting wheels help to provide finished cut by following the contours of the ground. The belt transmission with three equidistant high quality blades helps to provide excellent cut by working close to the ground.

#### **TECHNICAL SPECIFICATIONS**

| Model<br>Name | Overall<br>Length<br>(mm) | Cutting<br>Width<br>(mm) | Cutting<br>Height<br>(mm) | 3-point<br>Hitch<br>Type | Tractor<br>Power<br>(HP) | Wheel<br>Type            | Belt<br>(Number<br>& Type) | Number of blades | Blade<br>size (mm) | Blade<br>tip<br>Speed<br>(fpm) | Spindle<br>Type                   | Spindle<br>Bearings | Front roller | Deck<br>Thickness<br>(mm) | Weight<br>(Kg) |
|---------------|---------------------------|--------------------------|---------------------------|--------------------------|--------------------------|--------------------------|----------------------------|------------------|--------------------|--------------------------------|-----------------------------------|---------------------|--------------|---------------------------|----------------|
| SLGM-1.2      | 1370x1400x850             | 1210                     | 19-110                    | Cat-I/II                 | 16-50                    | Solid<br>Tyre<br>10x3.25 | 2 SPB<br>Type<br>1500      | 3                | 6x60x415           | 13585                          | With<br>Greasable<br>Ball Bearing | Bearing<br>6206     | 100x240      | 4                         | 205            |
| SLGM-1.5      | 1640x1540x850             | 1510                     | 19-110                    | Cat-I/II                 | 16-50                    | Solid<br>Tyre<br>10x3.25 | 2 SPB<br>Type<br>1500      | 3                | 6x60x515           | 14085                          | With<br>Greasable<br>Ball Bearing | Bearing<br>6206     | 100x240      | 4                         | 228            |
| SLGM-1.8      | 1890x1540x850             | 1805                     | 19-110                    | Cat-I/II                 | 20-50                    | Solid<br>Tyre<br>10x3.25 | 2 SPB<br>Type<br>1500      | 3                | 6x60x616           | 14192                          | With<br>Greasable<br>Ball Bearing | Bearing<br>6206     | 100x240      | 4                         | 253            |



RUGGED GEARBOX ENSURES EFFICIENT WORKING IN ALL CONDITIONS



EXTRA WIDE SOLID TYRES EASILY FOLLOW THE CONTOURS ALONG THE GROUND



ROLLOVER WHEEL AVOIDS EXTRA DAMAGE & PROVIDES EXTRA SUPPORT



SPACERS ENSURES EASY ADJUSTMENT OF HEIGHT



HIGH QUALITY TWISTED BLADES PROVIDES EVEN & SMOOTH CUT



# SONALIKA

#### INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India) Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221 Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com

Auth. Dealer