

# SONALIKA

**HEAVY DUTY  
TRACTOR RANGE**  
FOR YOUR FIELD

## N 60



ORCHARD/VINEYARD  
FARMING SPECIALIST

4 CYLINDER, NATURAL  
ASPIRATED ENGINE

HEAVY-LIFTING  
CAPACITY

SYNCHROMESH SHUTTLE  
TRANSMISSION WITH  
CREEPER

TWIN PROJECTOR  
HEADLAMPS



**COST  
EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL  
STEEL**

**STRATEGIC  
COLLABORATION  
WITH  
YANMAR**

# HEAVY DUTY TRACTOR RANGE

FOR YOUR FIELD

## N 60

# SONALIKA




FEATURES	Sonalika N 60
<b>ENGINE</b>	
Engine Type	4 Cylinder, Natural Aspirated Engine
HP Category	60
No. of Cylinders	4
Aspiration	Natural Aspirated
Cubic Capacity (cc)	3707
Rated RPM	2200
Air Cleaner	Dry Air Cleaner with Clogging Sensor
Cold Start	Yes
Max Torque (Nm) ± 5%	230@1200
Exhaust	Underhood Downdraft Towards the Floor
<b>TRANSMISSION</b>	
Clutch	Double Clutch
Gearbox	12F+12R
Front Axle	4WD
Transmission	Synchromesh Shuttle Transmission with Creeper
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	28.27@2200 erpm
Minimum Speed (Km/Hr)	0.46@2000 erpm
<b>BRAKES</b>	
Brakes	Oil Immersed Brake
Type of Actuation	Mechanical
Parking Brake	Independent Type
<b>DIFFERENTIAL LOCK</b>	
Differential Lock	Yes, Foot Operated
<b>PTO</b>	
PTO (RPM)	540/540E
PTO (Actuation)	Mechanical
<b>STEERING</b>	
Steering	Power
<b>ELECTRICAL</b>	
Battery	12V, 88Ah
Alternator	12V, 85Amp
Seven Pin Trailer Socket	Yes
<b>HYDRAULICS</b>	
3 Point Linkage	CAT-II
Stay Bars	Standard
Hydraulic Lifting Capacity (Kg)	2500
Auxiliary Hydraulic Circuit	2DA/2SA/3DA (Optional)

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

FEATURES	Sonalika N 60
<b>SAFETY SWITCH</b>	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
<b>CAPACITY (LTRS)(+/-5%)</b>	
Fuel Tank (Ltr.)	73
<b>TURNING RADIUS</b>	
Without Brakes (m)	4.58
<b>TYRE</b>	
Front	8-18
Rear	14.9-24
<b>DIMENSION (+/-5%) (4WD/2WD)</b>	
Weight (Kg)	2735
Overall Length (mm)	4252
Overall Width (mm)	1475-1606
Overall Height (mm)	2630
Wheel Base (mm)	2307
Min. Ground Clearance (mm)	256
Front Wheel Track Agri (mm)	1150-1606
Rear Wheel Track Agri (mm)	1082-1213
<b>OTHERS</b>	
Fuel Indicator Gauge	Standard
Front Tow Hook	Standard, Inbuilt in Front Weight
Front & Rear Weights with Std. Ballast	Front-72 Kg + 6x31 Kg Front Removal Weight. / Rear 1*30 Kg At Each Wheel
Trailer Hitch	Swinging Drawbar
ROPS	Optional
<b>OPTIONAL FEATURES</b>	
Tyres	4WD 1) Front Tyre: 260/70R16   Rear Tyre: 360/70R24 2) Front Tyre: 280/70R18   Rear Tyre: 360/70R28 3) Front Tyre: 280/70R18   Rear Tyre: 420/70R24 4) Front Tyre: 6.5x16   Rear Tyre: 360/70/R28 5) Front Tyre: 6.0x16   Rear Tyre: 360/70/R24 6) Front Tyre: 6.5x16   Rear Tyre: 420/70R24
Cabin	HVAC
Front Mudguard	Standard

DEALER STAMP



SONALIKA N60 AF

**INTERNATIONAL TRACTORS LIMITED**

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)

Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221

Fax:+91- 01882-522222 | Email: exports@sonalika.com | URL: www.international.sonalika.com