









DI-50 RX

FEATURES 50 4WD Model Description 50 4WD **ENGINE** Three Cylinder Natural Aspirated Engine **Engine Type HP Category** 50 No. of Cylinders 3 Aspiration Natural **Cold Start** Yes, Optional Cubic Capacity (cc) 3067 Rated RPM 2100 Air Cleaner Dry air cleaner with clogging sensor 205 (±5%) @ 1200 ± 100 Max Torque (nm) @ RPM Exhaust Updraft TRANSMISSION Drive 4WD **Dual Clutch** Clutch Gearbox 8F+2R Front Axle Dana Axle **Constant Mesh** Transmission SPEED (FORWARD) 2.46 Min Speed(km/h) Max Speed(km/h) 32.44 **BRAKES** Oil Immersed Brake Type of Actuation Mechanical **Hand Brake** Yes DIFFERENTIAL LOCK Dilerential Lock Yes, Foot Operated PTO Power Take O (RPM) 540 Power Take O ((Actuation) Mechanical **STEERING** Steering Power Steering ELECTRICAL 12V. 88Ah Battery 36 AMP, 12V Alternator Seven Pin Trailer Socket Yes **HYDRAULICS** 3 Point Linkage **CAT II Lifting Capacity** 1600Kg **Auxiliary Hydraulic Circuit** 1DA

SONALIKA



FEATURES	50 4WD
SAFETY SWITCH	
Clutch Safety Switch	Yes
CAPACITY (LTRS)(+/-5%)	
Fuel Tank	55
TURNING CIRCLE IN (M)	
Without Brakes	6.9
TYRE	Front:- 8-18, Rear:- 14.9-28
DIMENSION & WEIGHT(+/-5%)	
Gross Weight(kg)	2019 (Unballast Weight)
Wheel Base (mm)	2108
Total Length (mm)	3876
Total Width (mm)	1800
Height (mm) (upto Exhaust Pipe)	2281
Ground Clearance (mm) min	382
OTHERS	
Fuel Indicator Gauge	Yes
Front Tow Hook	Yes, inbuilt in front weight
Front & rear weights with std. Ballast	Base Weight 72Kg+Front 6X31 Kg
	Rear 1X34 Kg on each wheel
Trailer Hitch	Auto Trailer Hitch

^{*}Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

DEALER STAMP