## SONALIKA

• THE TOUGHEST • PERFORMER • « FOR YOUR FIELD » •

50 HP 2 WD



AGILE 3 CYLINDER ENGINE

OIL IMMERSED BRAKES

8F + 2R CONSTANTMESH TRANSMISSION

> HEAVY LIFT CAPACITY

> > SMART TECH FEATURES













## SONALIKA



FEATURES*	50 2WD
Model Description	50 2WD
ENGINE	
Engine Type	Three Cylinder Natural Aspirated Engine
HP Category	50
No. of Cylinders	3
Aspiration	Natural
Cold Start	No
Cubic Capacity (cc)	2893
Rated RPM	2100
Air Cleaner	Dry air cleaner with clogging sensor
Max Torque (nm) @ RPM	190 (±5%) @ 1200 ± 100
Exhaust	Updraft
TRANSMISSION	
Drive	2WD
Clutch	Single
Gearbox	8F+2R
Front Axle	Fixed Type
Transmission	Constant Mesh
SPEED (FORWARD)	
Min Speed(km/h)	3.04
Max Speed(km/h)	30.68
BRAKES	
Brakes	Oil Immersed Brake
Type of Actuation	Mechanical
Hand Brake	Yes
DIFFERENTIAL LOCK	
Differential Lock	Yes, Foot Operated
PTO	
Power Take Off (RPM)	540
Power Take Off (Actuation)	Mechanical
STEERING	
Steering	Power Steering
ELECTRICAL	
Battery	12V, 88Ah
Alternator	36 AMP, 12V
Seven Pin Trailer Socket	Yes
HYDRAULICS	
3 Point Linkage	CAT II
Lifting Capacity	1600Kg
Auxiliary Hydraulic Circuit	1SA

FEATURES	50 2WD
CAPACITY (LTRS)(+/-5%)	
Fuel Tank	55
TURNING CIRCLE IN (M)	
Without Brakes	7.41
TYRE	Front:- 6-16, Rear:- 13.6-28
DIMENSION & WEIGHT(+/-5%)	
Gross Weight(kg)	1837 (Unballast Weight)
Wheel Base (mm)	2074
Total Length (mm)	3880
Total Width (mm)	1776
Height (mm) (upto Exhaust Pipe)	2277
Ground Clearance (mm) min	392
OTHERS	
Fuel Indicator Gauge	Yes
Front Tow Hook	Yes, inbuilt in front weight
Front & rear weights with std. Ballast	Base Weight 72 Kg + 4*31 Kg
Trailer Hitch	Auto Trailer Hitch

<sup>\*</sup>Data and specifications are subject to change without any advance notice due to continuous product improvement and development.

**DEALER STAMP** 

## **INTERNATIONAL TRACTORS LIMITED**